


# Melville® 60 Slab




- Do not use vibrating plate
- Pedestrian - Designed to withstand pedestrian traffic
- Techniseal** 1 bag of sand covers approx. 155 ft<sup>2</sup>

## Melville® 60 Slab


|                     | DIMENSIONS (MM)            | DIMENSIONS (IN)           | CODES                   | COLOURS             | TYPICAL ROW |
|---------------------|----------------------------|---------------------------|-------------------------|---------------------|-------------|
| <b>A</b>            | 60 x 190 x 380             | 2 3/8 x 7 1/2 x 15        | <b>PRESTIGE COLOURS</b> |                     |             |
| <b>B</b>            | 60 x 380 x 380             | 2 3/8 x 15 x 15           | <b>12053046</b>         | Range Amber Beige   |             |
| <b>C</b>            | 60 x 380 x 570             | 2 3/8 x 15 x 22 7/16      | <b>12050265</b>         | Range Bayona Grey   |             |
| Weight/unit (avg.)  | 19 kg                      | 42 lb                     | <b>12052734</b>         | Range Margaux Beige |             |
| Unit/surface (avg.) | 0.14 unit/m <sup>2</sup>   | 1.46 unit/ft <sup>2</sup> | <b>12052104</b>         | Range Chambord Grey |             |
| Area/layer          | 1.08 m <sup>2</sup>        | 11.66 ft <sup>2</sup>     | <b>12052365</b>         | Range Scandina Grey |             |
| <b>Area/cube</b>    | <b>10.80 m<sup>2</sup></b> | <b>10 Rows</b>            | <b>12052733</b>         | Range Newport Grey  |             |
| Qty/cube            | 80 units                   | 80 units                  | <b>12053045</b>         | Range Shaded Grey   |             |
| Weight/cube         | 1538 kg                    | 3391 lb                   |                         |                     |             |
|                     |                            |                           |                         |                     |             |

Sold in full cubes only  
Can be double stacked  
Production location Cambridge

### LAYING PATTERNS



Modular



Linear

### TECHNICAL INFORMATION

| Product                 | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability  | Density | Absorption | Dimension Tolerance*   |
|-------------------------|------------|-------------------|----------------------|--|---------|------------|--|
| <b>Melville 60 Slab</b> | CSA A231.1 | ±4.5 MPa          | N/A                  | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.