


Melville® 60 Small Rectangle Paver



- Do not use vibrating plate
- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Techniseal** 1 bag of sand covers approx. 103 ft²

Melville® 60 Small Rectangle Paver




	DIMENSIONS (MM)	DIMENSIONS (IN)
	60 x 190 x 380	2 3/8 x 7 1/2 x 15
Weight/unit	10 kg	22 lb
Unit/surface	13.89 unit/m ²	1.29 unit/ft ²
Area/layer	0.87 m ²	9.33 ft ²
Area/cube	10.44 m²	12 Rows 111.96 ft²
Length/row Soldier	2.28 lin. m	7.48 lin. ft
Length/cube Soldier	27.36 lin. m	89.76 lin. ft
Qty/cube	144 units	144 units
Weight/cube	1465 kg	3225 lb


CODES	COLOURS
PRESTIGE COLOURS	
12053044	Range Amber Beige
12052446	Rockland Black
12052448	Range Scandina Grey
STANDARD COLOUR	
12053043	Range Shaded Grey
Sold in full cubes only	
Production location Cambridge	

TYPICAL ROW

LAYING PATTERNS



Linear



Herringbone

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Small Rectangle Paver	CSA A231.1	μ 50 MPa ≥ 45 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Melville 60 slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.