


Melville® 60 Textureguard Slab




- Do not use vibrating plate
- Pedestrian - Designed to withstand pedestrian traffic
- Techniseal** 1 bag of sand covers approx. 155 ft²


Melville® 60 Textureguard Slab

		DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
A		A	60 x 190 x 380	2 3/8 x 7 1/2 x 15	12051953 Marbella	
		B	60 x 380 x 380	2 3/8 x 15 x 15	12051954 Silverstone	
B		C	60 x 380 x 570	2 3/8 x 15 x 22 7/16	12051955 Hickory	
		Weight/unit (avg.)	20 kg	44 lb	Sold in full cubes only	
		Area/layer (avg.)	1.08 m ²	11.66 ft ²	Production location Metcalfe	
C		Area/cube	10.80 m²	10 Rows	116.60 ft²	
		Weight/cube	1603 kg	3535 lb		

LAYING PATTERNS



Modular



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Textureguard Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.