



Metrik Slab




- Do not use vibrating plate
- Pedestrian - Designed to withstand pedestrian traffic
- Techniseal** 1 bag of sand covers approx. 55 ft²


Metrik Slab

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
	60 x 70 x 280	2 3/8 x 2 3/4 x 11	PRESTIGE COLOURS		
Weight/unit	2.7 kg	5.96 lb	10502883	Range Bayona Grey (1)	
Surface/unit	0.02 m ²	0.21 ft ²	10502884	Blizzard (2)	
Area/layer	0.92 m ²	9.95 ft ²	10502882	Rockland Black (1)	
Area/cube	11.09 m²	12 Rows	Sold in full cubes only		
Qty/cube	576 units	576 units	Can be double stacked		
Weight/cube	1558 kg	3434 lb	Production locations:		
			Cambridge (1)		
			St-Eustache (2)		


LAYING PATTERNS




Checkerboard



Offset 1/2



Offset 1/3



Herringbone

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Metrik Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm