Mondrian® Plus 50 Slab










Do not use vibrating plate

Pedestrian - Designed to withstand pedestrian traffic


Techniseal 1 bag of sand covers approx. 186 ft²

Mondrian® Plus 50 Slab





	DIMENSION	IS (MM)	DIMENSIONS (IN)		
A	50 x 190 x	380	2 x 7 1/2 x 15		
В	50 x 380 x	380	2 x 15 x 15		
С	50 x 380 x	570	2 x 15 x 22 7/16		
Weight/unit (avg.)	16 kg		35 lb		
Surface/unit (avg.)	0.14 m ²		1.45 ft²		
Area/layer	1.08 m ²		11.66 ft ²		
Area/cube	10.80 m ²	10 Rows	116.60 ft ²		
Qty/cube	A = 30 B = 30		C = 20		
Weight/cube	1288 kg		2833 lb		

CODES	COLOURS				
PRESTIGE COLOUR					
12052842	Range Margaux Beige				
STANDARD COLOURS					
12052843	Range Norvick Grey				
12052841	Range Newport Grey				
Sold in full cubes only Production location Metcalfe					



LAYING PATTERNS





TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 50 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

 $^{^{\}star}$ Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.