


# Mondrian® Plus 60 Small Rectangle Paver



Slabs


- Do not use vibrating plate
- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Techniseal** 1 bag of sand covers approx. 38 ft<sup>2</sup>

## Mondrian® Plus 60 Small Rectangle Paver




|                     | DIMENSIONS (MM)           | DIMENSIONS (IN)           |
|---------------------|---------------------------|---------------------------|
|                     | 60 x 330 x 165            | 2 3/8 x 13 x 6 1/2        |
| Weight/unit         | 7.7 kg                    | 17 lb                     |
| Unit/surface        | 18.52 unit/m <sup>2</sup> | 1.71 unit/ft <sup>2</sup> |
| Area/layer          | 0.82 m <sup>2</sup>       | 8.79 ft <sup>2</sup>      |
| <b>Area/cube</b>    | <b>9.84 m<sup>2</sup></b> | <b>12 Rows</b>            |
| Length/row Soldier  | 2.48 lin. m               | 8.12 lin. ft              |
| Length/cube Soldier | 29.76 lin. m              | 97.44 lin. ft             |
| Qty/cube            | 180 units                 | 180 units                 |
| Weight/cube         | 1389 kg                   | 3062 lb                   |


| CODE                          | COLOUR         |
|-------------------------------|----------------|
| <b>PRESTIGE COLOUR</b>        |                |
| 12052557                      | Rockland Black |
| Sold in full cubes only       |                |
| Production location Cambridge |                |



### LAYING PATTERNS



Linear



Herringbone

### TECHNICAL INFORMATION

| Product                                       | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability  | Density | Absorption | Dimension Tolerance*   |
|---|------------|-------------------|----------------------|--|---------|------------|--|
| <b>Mondrian Plus 60 Small Rectangle Paver</b> | CSA A231.1 | ±4.5 MPa          | N/A                  | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
 Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.  
 Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.  
 The Mondrian Plus 60 slab is compatible with the Mondrian Plus 60 small rectangle paver for non-vehicular application only.